



WEVER & DUCRÉ
LIGHTING

BOX SUSPENDED 3.0 LED

214264W3

Project

Type

Notes

Quantity

Date

GENERAL

Ceiling

Suspended

Signal White

IP20

Interior

405 lm

RAL 9003^a

LED

2700 K

CRI 90

L80 / 50000 h

3-step binning

MR 0.53

MDER 0.48

OPTICAL

Beam angle 35°

PHYSICAL

Length 67 mm

Width 67 mm

Height 300 mm

0.83 kg

incl. 2.5 m suspension



ELECTRICAL

phase-cut dim


220 - 240 V

Total connected power 5.5 W


PC1

Safety distance 0.3 m

^a RAL Palette colors may deviate slightly due to production conditions.



LIGHT DISTRIBUTION





WEVER & DUCRÉ
LIGHTING

BOX SUSPENDED 3.0 LED

214264W3

CONE DIAGRAM


35°

h (m)	E0° (lx)	ø (m)
1	999	0.63
2	249	1.26
3	111	1.89
4	62	2.52
5	40	3.15

SUSPENSION OPTIONS

Invisible Ceiling Suspension System

COLOUR	L · W (MM)	ORDERCODE
Signal Black	140 · 66	9 0 0 1 5 1 9 5
Pure White	140 · 66	9 0 0 1 5 1 9 6



Single Suspension

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
Ceiling Base round	Signal Black	ø84 · 29	9 0 0 5 2 0 2 1
Ceiling Base round	Pure White	ø84 · 29	9 0 0 5 2 0 2 2



Single Ceiling Base

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
semi recessed	Pure White	ø84 · 72	9 0 0 5 2 0 2 6
semi recessed	Signal Black	ø84 · 72	9 0 0 5 2 0 2 7

