



WEVER & DUCRÉ
LIGHTING

BOX WALL mini 1.0

300120WN0

Project
Type
Notes
Quantity
Date

GENERAL

Wall
 Surface
 Walnut Wood
 IP20
 Interior
 410^a to 415^b lm

LED

Lamp PAR16
 PAR16
 Socket GU10
 max. 12 W
 CRI 80
 L70 / 50000 h



PHYSICAL

Length 70 mm
 Width 70 mm
 Height 115 mm
 0.24 kg


ELECTRICAL

100 - 240 V
 Total connected power 6.6^b to 6.7^a W
 PC1
 Safety distance 0.3 m

^a LED 3000K CRI 80 white
^b LED 2700K CRI 80 white



LIGHT DISTRIBUTION



[300120WN0] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BVBA apply.
 © Wever & Ducré BVBA · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com



WEVER & DUCRÉ
LIGHTING

BOX WALL mini 1.0

300120WN0

LED LAMPS

PAR16 LED Lamp

TYPE	COLOUR	Ø·H (MM)	ORDERCODE
2700K >90 CRI GU10	Jet Black	∅50·58	9 0 1 2 2 8 B 3
3000K >90 CRI GU10	Jet Black	∅50·58	9 0 1 2 2 8 B 5
2700K >80 CRI GU10	Signal White	∅50·58	9 0 1 2 2 8 W 2
2700K >90 CRI GU10	Signal White	∅50·58	9 0 1 2 2 8 W 3
3000K >80 CRI GU10	Signal White	∅50·58	9 0 1 2 2 8 W 4