



WEVER & DUCRÉ
LIGHTING

TAPE 4.0

722274W5

Project
Type
Notes
Quantity
Date

GENERAL

Floor
 Surface
 Signal White
 IP65
 Exterior
 420 lm
 RAL 9003^a

LED

3000 K
 CRI 90
 L95 / 50000 h
 3-step binning
 MR 0.59
 MDER 0.54

OPTICAL

Wide Flood


PHYSICAL

Length 180 mm
 Width 60 mm
 Height 400 mm
 1.92 kg

ELECTRICAL

phase-cut dim
 220 - 240 V
 Total connected power 8 W
 PC1
 Safety distance 0.3 m

^a RAL Palette colors may deviate slightly due to production conditions.





WEVER & DUCRÉ
LIGHTING

TAPE 4.0

722274W5

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.98	0.98	0.98	0.97
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

GROUND SPIKE

Ground Spike

TYPE	L · W · H (MM)	ORDERCODE
TAPE PACE	58 · 70 · 356	9 0 0 1 3 1 0 2