



WEVER & DUCRÉ
LIGHTING

LEENS 1.0

311174W5

Project

Type

Notes

Quantity

Date

GENERAL

Wall

Surface

Signal White

IP20

Interior

490 lm

RAL 9003^a

LED

3000 K

CRI 90

L95 / 50000 h

3-step binning

MR 0.59

MDER 0.54

OPTICAL

Wide Flood

PHYSICAL

Length 130 mm

Width 130 mm

Height 30 mm

1.11 kg

ELECTRICAL

phase-cut dim


220 - 240 V

Total connected power 8 W

PC1

Safety distance 0.3 m

^a RAL Palette colors may deviate slightly due to production conditions.





WEVER & DUCRÉ
LIGHTING

LEENS

1.0

311174W5

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.98	0.98	0.98	0.97
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.