



WEVER & DUCRÉ  
LIGHTING

# MIRBI 1.0

11458805

Project

Type

Notes

Quantity

Date

## GENERAL

Ceiling

Recessed

Clear/Opal PMMA

IP44

Interior

500 lm

RAL 9003<sup>a</sup>

## LED

3000 K

CRI 90

L70 / 50000 h

3-step binning

## PHYSICAL

Diameter 92 mm

Height 62 mm

0.24 kg

## ELECTRICAL

phase-cut dim

220 - 240 V

Total connected power 6.5 W

PC2

Safety distance 0.3 m

## CUTOUT



Diameter 76-79 mm

Min. ceiling thickness 8 mm

Max. ceiling thickness 15 mm

Recessed depth 50 mm

<sup>a</sup> RAL Palette colors may deviate slightly due to production conditions.





**WEVER & DUCRÉ**  
LIGHTING

# MIRBI 1.0

11458805

## Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.94	0.89	0.83	0.78	0.73
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF <sup>a</sup>	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF <sup>a</sup>	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

<sup>a</sup> According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

## Electrical

### DIMMER

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
DIMMER FOR SWITCH	Signal Black	18-48-46	9 0 0 1 9 0 1 7
DIMMER DIN RAIL	Pure White	55-17-90	9 0 0 1 9 0 1 8