



WEVER & DUCRÉ
LIGHTING

ORIS 0.7

327161B4

Project
Type
Notes
Quantity
Date

GENERAL

Wall
 Recessed
 Jet Black
 IP20
 Interior
 81^a to 140^b lm
 RAL 9005 ^c

LED

3000 K
 CRI 80
 L90 / 50000 h
 3-step binning

PHYSICAL

Length 65 mm
 Width 33 mm
 Height 200 mm
 0.28 kg

ELECTRICAL

excl. power supply
 3 V
 Total connected power 1.4^a to 2.9^b W
 350^a to 700^b mA
 PC3
 Safety distance 0.3 m



CUTOUT

Length 47 mm
 Width 182 mm
 Min. ceiling thickness 12 mm
 Max. ceiling thickness 40 mm
 Recessed depth 40 mm

^a 350mA

^b 700mA

^c RAL Palette colors may deviate slightly due to production conditions.





WEVER & DUCRÉ
LIGHTING

ORIS 0.7

327161B4

MOUNTING

Plasterkit + Recessed Housing

TYPE	L · W · H (MM)	ORDERCODE
ORIS 0.7	100 · 67 · 250	9 0 0 1 2 0 3 9

Concrete Housing

TYPE	L · W · H (MM)	ORDERCODE
ORIS 0.7	57 · 55 · 190	9 0 0 1 2 0 4 4

POWER SUPPLIES

Power Supply

TYPE	L · W · H (MM)	VOLTAGE	ORDERCODE
Driver 4W 350mA 4-12V	43 · 42 · 23		9 0 2 1 3 2 0 1
Driver 6W 350mA 3-22V	64 · 35 · 21	3 - 22V	9 0 2 1 3 2 0 2
Driver 6W 500mA 3-12V	64 · 35 · 21		9 0 2 1 4 2 0 1
Driver 6W 700mA 3-8.4V	64 · 35 · 21		9 0 2 1 5 2 0 3