



WEVER & DUCRÉ  
LIGHTING

# ORIS 2.0

327361B4

Project

Type

Notes

Quantity

Date

## GENERAL

Wall

Recessed

Jet Black

IP20

Interior

165<sup>a</sup> to 275<sup>b</sup> lm

RAL 9005<sup>c</sup>

## LED

3000 K

CRI 80

L90 / 50000 h

3-step binning

## PHYSICAL

Length 130 mm

Width 33 mm

Height 200 mm

0.42 kg

## ELECTRICAL

excl. power supply

6 V

Total connected power 2.7<sup>a</sup> to 5.8<sup>b</sup> W  
350<sup>a</sup> to 700<sup>b</sup> mA

PC3

Safety distance 0.3 m

## CUTOUT

Length 115 mm

Width 185 mm

Min. ceiling thickness 12 mm



Max. ceiling thickness 40 mm

Recessed depth 40 mm

<sup>a</sup> 350mA

<sup>b</sup> 700mA

<sup>c</sup> RAL Palette colors may deviate slightly due to production conditions.





WEVER & DUCRÉ  
LIGHTING

# ORIS 2.0

327361B4

## MOUNTING

### Concrete Housing

TYPE	L · W · H (MM)	ORDERCODE
ORIS 2.0	122·55·190	9 0 0 1 2 0 4 2

### Plasterkit + Recessed Housing

TYPE	L · W · H (MM)	ORDERCODE
ORIS 2.0	160·67·250	9 0 0 1 2 0 4 3

## POWER SUPPLIES

### Power Supply

TYPE	L · W · H (MM)	VOLTAGE	ORDERCODE
Driver 4W   350mA   4-12V	43·42·23		9 0 2 1 3 2 0 1
Driver 6W   350mA   3-22V	64·35·21	3 - 22V	9 0 2 1 3 2 0 2
Driver 6W   500mA   3-12V	64·35·21		9 0 2 1 4 2 0 1
Driver 6W   700mA   3-8.4V	64·35·21		9 0 2 1 5 2 0 3